



## 10A Single-Phase GLass Passivated Bridge Rectifiers

Recifier Reverse Voltage 50V to 1000V



**GBJ**



### Features

- Rating to 1000V PRV
- Ideal for printed circuit board
- Low forward voltage drop, high current capability
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- The plastic material has U/L flammability classification 94V-0
- Weight: 0.24ounce, 6.79 grams (approx)

### Maximum Ratings & Thermal Characteristics

Dimensions in inches and (millimeters)

Rating at 25°C ambient temperature unless otherwise specified, Resistive or inductive load, 60HZ.

For Capacitive load derate current by 20%

Parameter	Symbol	GBJ 10005	GBJ 1001	GBJ 1002	GBJ 1004	GBJ 1006	GBJ 1008	GBJ 1010	unit	
Maximum repetitive peak reverse voltage	VRRM	50	100	200	400	600	800	1000	V	
Maximum RMS bridge input voltage	VRMS	35	70	140	280	420	560	700	V	
Maximum DC blocking voltage	VDC	50	100	200	400	600	800	1000	V	
Maximum average forward rectified output current at TA=40°C	IF(AV)	10.0							3.0	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	220								A
Maximum instantaneous forward voltage drop per leg at 5A DC	VF	1.05								V
Maximum DC reverse current at ratde TA=25°C	IR	10								UA
DC blocking voltage per element TA=125°C		500								
Rating for fusing(t<8.3ms)	I <sup>2</sup> t	201								A <sup>2</sup> sec
Typical thermal resistance per element(1)	ReJA	1.4								°C/w
Mounting torque(Suggests 045~0.65)	Tor	Rating Torque:0.8(Suggests 045~0.65)								N.m
Typical thermal resistance per element(2)	Cj	55.0								PF
Operating junction and stroage temperature range	TJ, TSTG	-55to+150								°C

Notes:(1)Device mounted on 150mm\*150mm\*1.6mm Cu plate heatsink.

(2)Measured at 1.0MHz and applied reverse voltage of 4.0 volts.

## Rating and Characteristic Curves (TA=25°C Unless otherwise noted)

FIG.1-DERATING CURVE FOR




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL JUNCTION





FIG.4-TYPICAL FORWARD CHARACTERISTICS



PERCENT OF RATED PEAK REVERSE VOLTAGE, (%) CHARACTERISTICS

